

# Dry Area Anti-Fatigue Options

## **Cushion Max**™

#### **Complete Comfort**<sup>™</sup>

### **Complete Comfort™ II**

#### **DuraComfort**

### Hog Heaven®











Closed-cell nitrile/PVC-blended foam

molded to a solid nitrile surface

Material	Closed-cell nitrile/PVC-blended foam
Edges	Beveled
Thickness	5/8" (0.625")
Compression Deflection*	61.7% at 20 psi
Resistant to Grease/Oil & Chemicals	√
High-Heel Safe	
Welding Safe	

	Beveled	
	5/8" (0.625")	
n*	61.7% at 20 psi	
	V	
	No rating	
	Black	
	2' x 3' 3' x 12' 3' x 5' 4' x 6' Custom 2', 3', & 4' widths up to 45' in length are available.	

Closed-cell nitrile/PVC-blended foam	
Beveled	
5/8" (0.625")	
49.3% at 20 psi	
√	

oam	High-density, o nitrile fo	
	Bevelo	ed
	1/2" (0.	.5")
	50.5% at	20 psi
	√	
	√	
	√	
	√	
	Static diss	ipative
	Black	k
4' x 6' 4' x 8' 5' in	2' x 3' 3' x 4'	3' x 5' 4' x 6'

2' x 3'	3' x 5'
3' x 4'	4' x 6'

Closed-cell nitrile/PVC-blended foam encapsulated in solid nitrile rubber	

32.29

Beveled	Sloped
1/2" (0.5")	5/8" (0.625") or 7/8" (0.8750)

% at 20 psi	5/8" Mat: 47.8% at 20 ps 7/8" Mat: 51.0% at 20 ps

√	√
√	V

Licetifically conductive	LICCIII	carry cond	uctive
x / Available with OSHA-approved caution yellow borders	Black / Availa cautio	ble with OS on yellow bo	• • •
	2' x 3'	3' x 12'	4.8' x 8'

3' X 4'	4 X b
Custom 2', 3'	, 4' & 4.8' widths up to 100' in
length are av	ailable. Please note that mats
over 60'	will have up to 2 seams.

Flectrically conductive



**Anti-Microbial** 

**ESD Rating** 

**Color Options** 

**Available Sizes** 





No rating

Black

3' x 5'

3' x 10'

Custom 3' & 4' widths up to 7 length are available.

2' x 3'





Flectrically conductive

2' x 3'

3' x 5'

Black



<sup>\*</sup>Compression deflection is a measurement designed to assess and compare performance characteristics of anti-fatigue mats. A load is applied to the mat at 20 psi (equivalent to a 150-pound person standing) and the deflection is measured. Test results are reported as a percentage. Studies suggests that surfaces with a compression deflection of less than 20% are perceived as too hard, and surfaces greater than 60% can be perceived as too soft. Mats with a compression deflection between 20% and 60% tend to provide the most anti-fatigue benefits.